

AAW Lathe Safety Guidelines

Safe and effective use of a wood lathe requires study and knowledge of procedures for using this tool.

Always wear safety goggles or safety glasses that include side protectors and a full-face shield when needed. Wood dust can be harmful to your respiratory system. Use a dust mask or helmet and proper ventilation (dust collection system) in dusty work conditions. Wear hearing protection during extended periods of operation.

Tie back long hair, do not wear gloves, loose clothing, jewelry or any dangling objects that may catch in rotating parts or accessories.

Check the owner/operator's manual for proper speed recommendations. Use slower speeds for larger diameter or rough pieces and increased speed for smaller diameters and pieces that are balanced. If the lathe is shaking or vibrating, lower the speed. If the workpiece vibrates, always stop the machine to check the reason.

Make certain that the belt guard or cover is in place. Check that all clamping devices (locks), such as on the tailstock and toolrest, are tight.

Rotate your workpiece by hand to make sure it clears the toolrest and bed before turning the lathe "on". Be sure that the workpiece turns freely and is firmly mounted. It is always safest to turn the lathe "off" before adjusting the toolrest.

Exercise caution when using stock with racks, splits, checks, bark, knots, irregular shapes or protuberances.

Hold turning tools securely on the toolrest and hold the tool in a controlled but comfortable manner. Always use a slower speed when starting until the workpiece is balanced. This helps avoid the possibility of an unbalanced piece jumping out of the lathe and striking the operator.

When running a lathe in reverse. It is possible for a chuck or faceplate to unscrew unless it is securely tightened on the lathe spindle.

Know your capabilities and limits. An experienced wood turner may be capable of techniques and procedures not recommended for beginning turners.

When using a faceplate, be certain the workpiece is solidly mounted. When turning between centers, be certain the workpiece is secure.

Always remove the toolrest before sanding or polishing operation.

Don't overreach, keep proper footing and balance at all times.

Keep lathe in good repair. Check for damaged parts, alignment, binding of moving parts and other conditions that may affect its operation.

Keep tools sharp and clean for better and safer performance. Don't force a dull tool. Don't use a tool for a purpose not intended. Keep tools out of the reach of children.

Consider your work environment. Don't use a lathe in a damp or wet location. Do not use in the presence of flammable liquids or gases. Keep work area well lit.

Stay alert. Watch what you are doing, use common sense. Don't operate your tools when you are tired or under the influence of drugs or alcohol.

Guard against electric shock. Inspect electric cords for damage. Avoid the use of extension cords.

Remove chuck keys and adjusting wrenches. Form a habit of checking for these before switching on the lathe.

Never leave the lathe unattended. Turn power off. Don't leave the lathe until it comes to a complete stop.